

# Rugged Handheld Device 7"

**M700D**

Model Name : M700D

## Product Features:

- Intel® Atom™ Processor Dual Core N2600 1.6 GHz
- 7"WSVGA(1024x600)TFT LCD Display
- Compliant with MIL-STD-810G
- Projected Capacitive Multi-Touch Screen
- 2.0M Camera in Rear Side (with LED auxiliary light, Auto Focus)
- G-sensor and Light sensor
- Built-in WLAN 802.11 a/b/g/n & Bluetooth 4.0 & Neo-6 GPS
- Support Windows® Embedded Standard 7 Operating System




## Product Specifications:

System Specification	Processor	Intel® Atom™ Processor N2600 1.6 GHz
	System Memory	2 GB DDR3 SDRAM(upgradable to 4 GB)
	Storage	32GB SSD(upgradable to 128 GB SSD)
	Operating System	Windows® Embedded Standard 7 (WES7P)
Display Specification	Size	7"
	Resolution	1024 * 600
	Brightness	500nit (typ.)
	Touch	Projected Capacitive Touch
Wireless Communication	WLAN	Support 802.11 a/b/g/n 2T2R
	Bluetooth	Bluetooth 4.0 + Class I
	WWAN	Optional 3G(support HSPA/ UMTS / GPRS / WCDMA / GSM)
	GPS	Neo-6 GPS Module
Mechanical and Environment	Dimensions (W x L x H)	212.4 x 132.8 x 25 mm (Standard)
	Weight	770g (Standard) / 1070g (with second battery)
	Operation Temperature	-20°C to 60°C (AC mode), -10°C to 50°C (Battery mode)
	Operation Humidity	95% RH (non condensing)
	IP Proof	IP65
	Shock	MIL-STD-810G Method 516.6
	Vibration	MIL-STD-810G Method 514.6
	Drop	MIL-STD-810G Method 516.6, 4 ft, Free to concrete
Certifications	CE, FCC	
I/O Connectors	External I/O	1 x USB 2.0 A Type 1 x Headset jack 1 x 2.5Ø 12V DC Power Input 1 x SIM Slot 1 x Micro SD Card 1 x Docking Port (For charge and USB) 1 x Secondary Battery Connector
	Internal Audio Device	1.2W Speaker
Power Management	Power input	12V DC in
	Power consumption	11.5W (under full loading)
	Battery	7.4V 2270mAh Li-Poly rechargeable battery 2S1P 7.4V 5300mAh Hotswap second battery 2S1P
	Battery Operating Time	Main Battery: 3hrs* With Second Battery: 10hrs*
	Adapter	50W Adapter
Field Service Features	Camera	2.0M pixel Camera with LED auxiliary light(Rear Side , with Auto Focus)

\* Note: Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.

## Dimensions :



Accessories:	
Default	Quick Start Guide
	User Manual
	50W Adapter
	5300mAh Second battery

Order Information:	
Model Name	Configuration
M700D	Standard
M700D-3	with 3G card