

E430RM4-3HF Specifications

Display Specifications

Size	4.3"
Brightness	400(typ.)
Resolution	480 x 800
Contrast Ratio	800:1 (typ.)
Touch	Projective Capacitive Multi-touch
Sensors	Light Sensor, Proximity Sensor, G-sensor, Digital Compass

System Specification

Processor	ARM® Cortex™-A7 Quad Core 1.5Ghz
Memory	1GB SDRAM
Storage	4GB eMMC(Optional to 32GB, MOQ:1K)
Audio	1 x Built-in Mic, 1 x Earphone, 1 x 1.2W Speaker

Wireless Communication

WLAN	Support 802.11 a/b/g/n
Bluetooth	Bluetooth V3.0
WWAN	GSM / GPRS / EDGE / WCDMA / HSDPA / HSUPA
GPS	Built-in GPS module

In front Control

	1 x Volume - + 1 x Power button
Control Button	1 x Function button 4 xCapacitive buttons:Home/ Menu/ ESC/ Search functions
LED indicator	1 x LED indicator

Mechanical and Environment

Dimensions (W x L x H)	132.57 x 81.87 x 27.4 mm
Operating Temperature	-10 deg.C to 50 deg.C(Battery Mode)
IP Proof	IP65
Certifications	CE, FCC, CCC
Gross Weight(kg)	275g
Shock	MIL-STD-810G Method 516.6 Procedure I
Vibration	MIL-STD-810G Method 514.6 Procedure I
Drop	MIL-STD-810G Method 516.6, 4 ft, Free to concrete

Power Management

Battery	3.7V 3900mAh Li-poly removable battery
Adapter	5V/1A , USB Adapter
Battery Operating Time	20 hrs **

Product Specification

OS	Android 4.2
RFID	RF Transmit Frequency 13.56MHz ISO 14443-A(R/W) ISO 15693(R/W)) Mifare_One(S50), Mifare_One(S70)
Camera	Rear: 8 Mega-Pixel Camera with LED auxiliary light (Auto Focus) Front: 2 Mega-Pixel Camera

- *The weight information is for reference purpose.The actual weight will vary according to then options you choose,for example,the touch/glass option.
- **Note: Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
- Note: All Specifications are subject to change without prior notice.